

EXHIBIT A

TO

COMPLAINT

**U.S. Patent No.
10,710,545 and
Ex Parte Reexamination
Certificate 10,710,545 C1**



US010710545B2

(12) **United States Patent**
Friedman

(10) **Patent No.:** **US 10,710,545 B2**
(45) **Date of Patent:** ***Jul. 14, 2020**

(54) **LOCKING HARNESS**

(71) Applicant: **FRIEDMAN IP HOLDINGS, LLC**,
Niskayuna, NY (US)

(72) Inventor: **Mark J. Friedman**, Niskayuna, NY
(US)

(73) Assignee: **Friedman IP Holdings, LLC**,
Niskayuna, NY (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 46 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/273,291**

(22) Filed: **Feb. 12, 2019**

(65) **Prior Publication Data**

US 2019/0168706 A1 Jun. 6, 2019

Related U.S. Application Data

(60) Continuation of application No. 15/602,294, filed on
May 23, 2017, now Pat. No. 10,259,423, which is a
continuation of application No. 14/984,232, filed on
Dec. 30, 2015, now Pat. No. 9,669,797, which is a
continuation of application No. 14/481,016, filed on
Sep. 9, 2014, now Pat. No. 9,561,776, which is a
division of application No. 13/653,540, filed on Oct.
17, 2012, now Pat. No. 8,851,575, which is a division
(Continued)

(51) **Int. Cl.**
B60R 22/48 (2006.01)
B60R 22/12 (2006.01)
B60N 2/28 (2006.01)
B60R 22/10 (2006.01)
B60R 22/36 (2006.01)

(52) **U.S. Cl.**

CPC **B60R 22/12** (2013.01); **B60N 2/2803**
(2013.01); **B60N 2/2812** (2013.01); **B60R**
22/105 (2013.01); **B60R 22/36** (2013.01);
B60R 22/48 (2013.01); **A44D 2200/12**
(2013.01); **B60N 2002/2815** (2013.01); **Y10S**
24/38 (2013.01); **Y10T 24/4012** (2015.01);
Y10T 24/45529 (2015.01); **Y10T 29/49826**
(2015.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,594,006 A 11/1897 Gorton
2,084,412 A 6/1937 Schaefer
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2008105552 5/2005


Primary Examiner — David E Allred

(74) *Attorney, Agent, or Firm* — Mark J. Friedman

(57) **ABSTRACT**

A retainer apparatus including a first retainer portion, a second retainer portion, and a sensor comprising a motion detector and an alarm. The retainer apparatus includes the first retainer portion configured to be slidably attached to a first harness strap and a second retainer portion configured to be slidably attached to a second harness strap. The first retainer portion is removably attached to the second retainer portion. The motion detector is configured to detect movement of the retainer apparatus and activate the alarm to alert a user in a vehicle if movement of the retainer apparatus is detected.

20 Claims, 7 Drawing Sheets



US 10,710,545 B2

Page 2

Related U.S. Application Data

of application No. 12/703,227, filed on Feb. 10, 2010,
now Pat. No. 8,333,433.

(56)

References Cited

U.S. PATENT DOCUMENTS

2,228,379 A	1/1941	Woodard	7,340,809 B2 *	3/2008	Tracy	B60N 2/2812
2,403,712 A	7/1946	Elwell	7,367,092 B1	5/2008	Dilday	200/61.58 B
3,586,220 A	6/1971	Reinsberg	7,445,293 B2	11/2008	Smith et al.	
3,649,076 A	3/1972	Blake	7,466,221 B1	12/2008	Lehr	
3,672,004 A	6/1972	Smith	7,642,907 B2	1/2010	Tang et al.	
3,872,197 A	3/1975	Kato et al.	7,964,130 B2	6/2011	You	
3,988,098 A	10/1976	Kato et al.	8,195,365 B2	6/2012	Bernhagen et al.	
3,996,929 A	12/1976	Mabuchi	8,262,133 B2	9/2012	Usoro et al.	
4,323,204 A	4/1982	Takada	8,333,433 B2	12/2012	Friedman	
4,491,343 A	1/1985	Foehl	8,648,735 B2	2/2014	Haynes et al.	
4,492,348 A	1/1985	Ziv et al.	8,659,414 B1 *	2/2014	Schuk	G08B 21/22
4,554,779 A	11/1985	Fischer	8,714,114 B1	5/2014	Wang et al.	340/457
4,569,106 A	2/1986	Lovato	8,851,575 B2	10/2014	Friedman	
4,569,629 A	2/1986	Ferris et al.	9,440,777 B2	9/2016	Friedman	
4,800,629 A	1/1989	Ikeda	9,539,983 B2 *	1/2017	Demeritte	B60R 22/48
4,810,036 A	3/1989	Buser	9,669,797 B2	6/2017	Friedman	
4,973,083 A	11/1990	Richards et al.	10,127,742 B2 *	11/2018	Seibert	H04L 67/12
5,029,896 A	7/1991	Ernst	10,173,640 B1 *	1/2019	Zhang	B60R 22/48
5,037,135 A	8/1991	Kotikovskiy et al.	2002/0029443 A1	3/2002	Ortiz	
5,151,678 A	9/1992	Veltri et al.	2003/0075969 A1	4/2003	Fromme et al.	
5,411,292 A	5/1995	Collins et al.	2003/0122662 A1	7/2003	Quinonez	
5,498,017 A	3/1996	Rohrmoser	2003/0160689 A1	8/2003	Yazdgerdi	
5,566,427 A	10/1996	Lathrop	2005/0091808 A1	5/2005	Uehara et al.	
5,669,118 A	9/1997	Frano et al.	2005/0229867 A1	10/2005	Green	
5,735,024 A	4/1998	Ortiz	2005/0280297 A1	12/2005	Patterson et al.	
5,774,947 A	7/1998	Anscher	2006/0218761 A1	10/2006	Anscher	
5,839,789 A	11/1998	Koledin	2006/0231373 A1	10/2006	Taylor et al.	
5,839,793 A	11/1998	Merrick et al.	2006/0289575 A1	12/2006	Chou	
5,852,852 A	12/1998	Rigal	2007/0096891 A1	5/2007	Sheriff et al.	
5,873,635 A	2/1999	Merrick	2007/0102989 A1	5/2007	Smith et al.	
6,002,325 A	12/1999	Conaway	2007/0102990 A1	5/2007	Smith et al.	
6,079,662 A	6/2000	Miller et al.	2007/0193004 A1	8/2007	Chou	
6,079,744 A	6/2000	Husby et al.	2007/0283540 A1	12/2007	Chang	
6,142,524 A	11/2000	Brown et al.	2008/0223888 A1	9/2008	Meunier	
6,220,662 B1	4/2001	Franco-Vila et al.	2009/0079557 A1	3/2009	Miner	
6,357,091 B1	3/2002	Devereaux	2009/0179406 A1	7/2009	Haraoka et al.	
6,367,882 B1	4/2002	Van Druff et al.	2010/0244543 A1	9/2010	Fine et al.	
6,447,060 B1	9/2002	Vila et al.	2010/0253498 A1	10/2010	Rork et al.	
6,543,097 B2	4/2003	Burt et al.	2011/0193396 A1	8/2011	Friedman	
6,662,413 B2	12/2003	Glover	2013/0038101 A1	2/2013	Friedman	
6,809,640 B1 *	10/2004	Sherman	2013/0291344 A1	11/2013	Hortnagl	
			2014/0035338 A1	2/2014	Greenwood et al.	
6,824,222 B2	11/2004	Maloney et al.	2014/0375093 A1	12/2014	Friedman	
6,853,298 B1 *	2/2005	Stojanowski	2015/0013619 A1	1/2015	Kahana, Jr.	
			2015/0113770 A1	4/2015	Laatz	
6,922,154 B2	7/2005	Kraljic et al.	2015/0209052 A1	7/2015	Hopman et al.	
			2016/0107607 A1	4/2016	Friedman	
			2016/0183636 A1	6/2016	Laatz	
			2017/0273694 A1 *	9/2017	Lynch	G16H 40/63
			2017/0274867 A1	9/2017	Friedman	
			2017/0290530 A1 *	10/2017	Hong	A61B 5/1116

* cited by examiner

U.S. Patent

Jul. 14, 2020

Sheet 1 of 7

US 10,710,545 B2




FIG. 1




FIG. 2

U.S. Patent

Jul. 14, 2020

Sheet 3 of 7

US 10,710,545 B2




FIG. 3




FIG. 4A




FIG. 4B

U.S. Patent

Jul. 14, 2020

Sheet 5 of 7

US 10,710,545 B2




FIG. 4C

U.S. Patent

Jul. 14, 2020

Sheet 6 of 7

US 10,710,545 B2






FIG. 4D

U.S. Patent

Jul. 14, 2020

Sheet 7 of 7

US 10,710,545 B2



US 10,710,545 B2

1

LOCKING HARNESS**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a divisional application claiming priority to Ser. No. 15/602,294 filed on May 23, 2017 which is a continuation application claiming priority to Ser. No. 14/984,232 filed Dec. 30, 2015, now U.S. Pat. No. 9,669,797 issued Jun. 6, 2017 which is a continuation application claiming priority to Ser. No. 14/481,016 filed Sep. 9, 2014, now U.S. Pat. No. 9,561,776 issued Feb. 7, 2017 which is a divisional application claiming priority to Ser. No. 13/653,540 filed Oct. 17, 2012, now U.S. Pat. No. 8,851,575 issued Oct. 7, 2014 which is a divisional application of Ser. No. 12/703,227 filed Feb. 10, 2010, and entitled "Locking Harness Apparatus and Method", now U.S. Pat. No. 8,333,433, issued Dec. 18, 2012.

FIELD OF TECHNOLOGY

The present invention relates to a locking restraint apparatus and associated method for restraining an individual in a vehicle for preventing motion related injuries.

BACKGROUND

Restraining users during travel typically comprises an inefficient process with little flexibility. Accordingly, there exists a need in the art to overcome at least some of the deficiencies and limitations described herein above.

SUMMARY

The present invention provides a retainer apparatus comprising: a first retainer portion configured to be slidably attached to a first adjustable harness strap of a car seat; a second retainer portion configured to be slidably attached to a second adjustable harness strap of the car seat, wherein the first retainer portion is removably attached to the second retainer portion; a sensor comprising a motion detector and an alarm, wherein the motion detector is configured to detect movement of the retainer apparatus, and wherein the motion detector is configured to activate the alarm to alert a user in the vehicle if the movement of the retainer apparatus is detected; and a braking mechanism configured to resist the movement of the first retainer portion and the second retainer portion along the first adjustable harness strap and the second adjustable harness strap, wherein the braking mechanism comprises a braking device comprising braking portions configured for locking together thereby contacting opposite surfaces of the first adjustable harness strap and the second adjustable harness strap for applying resistance to the first adjustable harness strap and the second adjustable harness strap to hold at least one of the first retainer portion and the second retainer portion in a first stationary position along at least one of the first adjustable harness strap and the second adjustable harness strap, wherein the braking mechanism further comprises a locking portion configured to apply mechanical pressure and lock the braking portions of the braking device, and wherein the sensor and the braking mechanism are contained within at least one of the first retainer portion and the second retainer portion.

The present invention provides a car seat apparatus comprising: a first adjustable harness strap; a second adjustable harness strap; a retainer apparatus comprising a first retainer portion slidably attached to the first harness strap and a

2

second retainer portion slidably attached to the second harness strap, wherein the first retainer portion is removably attached to the second retainer portion, wherein the retainer apparatus further comprises a sensor comprising a motion detector and an alarm, wherein the motion detector is configured to detect movement of the retainer apparatus, and wherein the motion detector is configured to activate the alarm to alert a user in the vehicle if the movement of the retainer apparatus is detected, wherein the retainer apparatus further comprises a braking mechanism configured to resist the movement of the first retainer portion and the second retainer portion along the first adjustable harness strap and the second adjustable harness strap, wherein the braking mechanism comprises a braking device comprising braking portions configured for locking together thereby contacting opposite surfaces of the first adjustable harness strap and the second adjustable harness strap for applying resistance to the first adjustable harness strap and the second adjustable harness strap to hold at least one of the first retainer portion and the second retainer portion in a first stationary position along at least one of the first adjustable harness strap and the second adjustable harness strap, wherein the braking mechanism further comprises a locking portion configured to apply mechanical pressure and lock the braking portions of the braking device, and wherein the sensor and the braking mechanism are contained within at least one of the first retainer portion and the second retainer portion; and a car seat structure comprising a harness apparatus mechanically attached to the car seat structure, wherein the retainer apparatus, the first adjustable harness strap, and the second adjustable harness strap are comprised by the harness apparatus, and wherein the harness apparatus is configured to restrain an occupant of the car seat apparatus and prevent the occupant from being ejected from the car seat apparatus.

The present invention provides a retainer apparatus comprising: a first retainer portion configured to be slidably attached to a first adjustable harness strap of a car seat; a second retainer portion configured to be slidably attached to a second adjustable harness strap of the car seat, wherein the first retainer portion is removably attached to the second retainer portion; and a sensor comprising a motion detector and an alarm, wherein the motion detector is configured to detect movement of the retainer apparatus, wherein the motion detector is configured to activate the alarm to alert a user in the vehicle if the movement of the retainer apparatus is detected, and wherein the sensor is contained within at least one of the first retainer portion and the second retainer portion.

The present invention advantageously provides a simple apparatus and associated method capable of restraining users during travel.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a locking restraint apparatus for safely restraining an individual during travel in a vehicle, in accordance with embodiments of the present invention.

FIG. 2 illustrates the restraint apparatus of FIG. 1 safely restraining an individual during travel in a vehicle, in accordance with embodiments of the present invention.

FIG. 3 illustrates a close up view of the retainer apparatus 8 of FIG. 1 slidably attached to adjustable harness straps, in accordance with embodiments of the present invention.

FIG. 4A illustrates an alternative to FIG. 3, in accordance with embodiments of the present invention.

US 10,710,545 B2

3

FIG. 4B illustrates a cross sectional view of the retainer apparatus of FIG. 4A, in accordance with embodiments of the present invention.

FIG. 4C illustrates a first alternative cross sectional view of the retainer apparatus of FIG. 4B, in accordance with embodiments of the present invention.

FIG. 4D illustrates a second alternative cross sectional view of the retainer apparatus of FIG. 4B, in accordance with embodiments of the present invention.

FIG. 5A illustrates an alternative to FIG. 4A, in accordance with embodiments of the present invention.

FIG. 5B illustrates a cross sectional view of the retainer apparatus of FIG. 5A, in accordance with embodiments of the present invention.

DETAILED DESCRIPTION

FIG. 1 illustrates a restraint apparatus 1 for safely restraining an individual (e.g., a person) during travel in a vehicle, in accordance with embodiments of the present invention. Restraint apparatus 1 may be used in any type of vehicle including, inter alia, an automobile, an aircraft, a boat, etc. Restraint apparatus 1 comprises a seat structure 10 (e.g., a car seat), an adjustable harness strap 4a, an adjustable harness strap 4b, a retainer apparatus 8 slidably attached to adjustable harness strap 4a and adjustable harness strap 4b, and a harness portion 12. Adjustable harness strap 4a and adjustable harness strap 4b are configured to restrain an upper body portion of a person (e.g., see upper body portion 17a child 14 in FIG. 2, infra). An upper body portion (e.g., upper body portion 17a in FIG. 2) is defined herein as any portion of a body located above (i.e., in direction 20) a waist section (e.g., see waist section 17 in FIG. 2, infra). Adjustable harness strap 4a is removably attached to seat structure 10. Adjustable harness strap 4a extends from seat structure 10 through opening 30a to buckle structure 7. Adjustable harness strap 4a is removably attached to buckle structure 7. Adjustable harness strap 4b is removably attached to seat structure 10. Adjustable harness strap 4b extends from seat structure 10 through opening 30b to buckle structure 7. Adjustable harness strap 4b is removably attached to buckle structure 7. Retainer apparatus 8 comprises a retainer portion 8a, a retainer portion 8b, a braking mechanism 31, an optional motion detector/sensor/alarm apparatus 40, and an optional electrical motor/signal receiving device 34. Retainer portion 8a is slidably attached to harness strap 4a. Retainer portion 8b is slidably attached to harness strap 4b. Retainer apparatus 8 is configured to slidably move along harness strap 4a and harness strap 4b in a direction 20 and 22 and between ends 19a and 19b of harness strap 4a and ends 21a and 21b of harness strap 4b. Braking mechanism 31 is configured to adjustably prevent retainer portion 8a and retainer portion 8b from slidably moving along 4a harness strap and harness strap 4b. Braking mechanism 31 is configured to hold retainer portion 8a and retainer portion 8b at any stationary position along harness strap 4a and harness strap 4b. Braking mechanism 31 is configured to hold retainer portion 8a at any stationary position between portion 19a and portion 19b of harness strap 4a. Braking mechanism 31 is configured to hold retainer portion 8b at any stationary position between portion 21a and portion 21b of harness strap 4b. Retainer portion 8a is removably attached to retainer portion 8b (e.g., using clips 11a and 11b removably attached to openings 15a and 15b respectively as illustrated in FIGS. 3 and 4A, infra). Braking mechanism 31 comprises a braking device(s) (e.g. devices 37a, 37b, 38a, and 38b in FIG. 4B as described, infra) for applying resis-

4

tance to harness strap 4a and/or harness strap 4b for holding retainer apparatus 8 in any stationary position along harness strap 4a and harness strap 4b. Optional electrical motor/signal receiving device 34 may comprise a signal receiving/transmitting device (e.g., a wireless transceiver) and/or an electrical motor or solenoid. Optional electrical motor/signal receiving device 34 is configured to accept a control signal (i.e., via a signal receiving/transmitting device) from a control device (e.g., a computer/controller in a vehicle) and automatically (e.g., in accordance with the control signal enabled by a user) slidably move (i.e., using an electrical motor) retainer apparatus 8 along harness strap 4a and harness strap 4b in direction 20 and/or 22 until a disable control signal is received by the signal receiving/transmitting device. Alternatively, optional electrical motor/signal receiving device 34 may be configured to accept a control signal (i.e., via a signal receiving/transmitting device) from a control device (e.g., a computer/controller in a vehicle) and automatically (e.g., in accordance with the control signal enabled by a user) slidably move (i.e., using an electrical motor) retainer apparatus 8 along harness strap 4a and harness strap 4b (i.e., in direction 20 and/or 22) a predetermined or specified distance (e.g., data comprising specified distances may be stored within a memory structure located within retainer apparatus 8 and/or a computer/controller in a vehicle). Optional motion detector sensor/alarm apparatus 40 may comprise a motion detector and/or an alarm. The motion detector detects any movement of retainer apparatus 8 (e.g., in direction 20 or 22, retainer portion 8a disconnected from retainer portion 8b, etc) and either activates a warning alarm located within sensor/alarm apparatus 40 or transmits a warning signal to a computer/controller in a vehicle to warn a user (e.g., a driver) that movement of retainer apparatus 8 has been detected thereby allowing the user to re-secure an individual (e.g., a child) in restraint apparatus 1. Harness portion 12 comprises a first portion 12a, a second portion 12b, and a third portion 12c mechanically attached (i.e., removably or not removably) to buckle structure 7. Harness portion 12 is configured to restrain a lower body portion of a person (e.g., see lower body portion 17b of child 14 in FIG. 2, infra). A lower body portion (e.g., lower body portion 17b in FIG. 2) is defined herein as any portion of a body located below (i.e., in direction 22) a waist section (e.g., see waist section 17 in FIG. 2, infra). Restraint apparatus 1 may additionally comprise an additional retainer apparatus(s) (i.e., not shown and similar to or the same as retainer apparatus 8 comprising braking mechanism 31) slidably attached to adjustable harness strap 4a and adjustable harness strap 4b to provide additional restraint capabilities for restraint apparatus 1.

FIG. 2 illustrates restraint apparatus 1 of FIG. 1 safely restraining an individual 14 during travel in a vehicle, in accordance with embodiments of the present invention. Individual 14 comprises a waist section 17 used to define an upper body portion 17a and a lower body portion 17b. Additionally, FIG. 2 illustrates an optional additional retainer apparatus(s) 210 (i.e., similar to retainer apparatus 8 as described with respect to FIG. 1, supra) slidably attached to adjustable harness strap 4a and adjustable harness strap 4b to provide additional restraint capabilities for restraint apparatus 1. Similar to retainer apparatus 8 of FIG. 1, retainer apparatus 210 (of FIG. 2) comprises a retainer portion 210a, a retainer portion 210b, a braking mechanism 211, an optional motion detector/sensor/alarm apparatus 218, and an optional electrical motor/signal receiving device 200. Retainer portion 210a is slidably attached to harness strap 4a. Retainer portion 210b is slidably attached to

US 10,710,545 B2

5

harness strap 4b. Retainer apparatus 210 is configured to slidably move along harness strap 4a and harness strap 4b in directions 20 and 22. Braking mechanism 211 is configured to adjustably prevent retainer portion 210a and retainer portion 210b from slidably moving along 4a harness strap and harness strap 4b. Braking mechanism 211 is configured to hold retainer portion 210a and retainer portion 210b at any stationary position along harness strap 4a and harness strap 4b. Retainer portion 210a is removably attached to retainer portion 210b (e.g., using clips 224a and 224b 10 removably attached to openings 214a and 214b respectively as illustrated in FIG. 3, *infra*). Optional electrical motor/signal receiving device 200 may comprise a signal receiving/transmitting device (e.g., a wireless transceiver) and/or an electrical motor or solenoid. Optional electrical motor/signal receiving device 200 is configured to accept a control signal (i.e., via a signal receiving/transmitting device) from a control device (e.g., a computer/controller in a vehicle) and automatically (e.g., in accordance with the control signal enabled by a user) slidably move (i.e., using an electrical 20 motor) retainer apparatus 210 along harness strap 4a and harness strap 4b in direction 20 and/or 22 until a disable control signal is received by the signal receiving/transmitting device. Alternatively, optional electrical motor/signal receiving device 200 may be configured to accept a control signal (i.e., via a signal receiving/transmitting device) from a control device (e.g., a computer/controller in a vehicle) and automatically (e.g., in accordance with the control signal enabled by a user) slidably move (i.e., using an electrical 25 motor) retainer apparatus 210 along harness strap 4a and harness strap 4b (i.e., in direction 20 and/or 22) a predetermined or specified distance (e.g., data comprising specified distances may be stored within a memory structure located within retainer apparatus 210 and/or a computer/controller in a vehicle). Optional motion detector sensor/alarm apparatus 218 may comprise a motion detector and/or an alarm. The motion detector detects any movement of retainer apparatus 210 (e.g., in direction 20 or 22, retainer portion 210a disconnected from retainer portion 210b, etc) and either activates a warning alarm located within sensor/alarm 40 apparatus 218 or transmits a warning signal to a computer/controller in a vehicle to warn a user (e.g., a driver) that movement of retainer apparatus 210 has been detected thereby allowing the user to re-secure an individual (e.g., a child) in restraint apparatus 1.

FIG. 3 illustrates a close up view of retainer apparatus 8 of FIG. 1 and optional retainer apparatus 210 of FIG. 2 slidably attached to adjustable harness strap 4a and adjustable harness strap 4b, in accordance with embodiments of the present invention. In FIG. 3, retainer portion 8a is disconnected from retainer portion 8b. Retainer portion 8a is disconnected from retainer portion 8b by disabling using clips 11a and 11b from openings 15a and 15b, respectively. Retainer portion 8a is moved towards retainer portion 8b in a direction 60 and retainer portion 8b is moved towards 50 retainer portion 8a in a direction 61 in order to latch clip 11b to opening 15a and latch clip 11a to opening 15b (i.e., as illustrated in FIG. 4, *infra*). FIG. 3 additionally illustrates a close up view of braking mechanism 31 (i.e., comprising braking mechanism portions 31a and 31b), optional motion detector sensor/alarm apparatus 40 (i.e., comprising motion detector sensor/alarm apparatus portions 40a and 40b), and optional electrical motor/signal receiving device 34 (i.e., comprising electrical motor/signal receiving device portions 34a and 34b). Each of braking mechanism portion 31a, 65 motion detector sensor/alarm apparatus portion 40a, and electrical motor/signal receiving device portion 34a is

6

mechanically attached to retainer portion 8a. Each of braking mechanism portion 31b, motion detector sensor/alarm apparatus portion 40b, and electrical motor/signal receiving device portion 34b is mechanically attached to retainer portion 8b. Additionally, in FIG. 3, retainer portion 210a is disconnected from retainer portion 210b. Retainer portion 210a is disconnected from retainer portion 210b by disabling clips 224a and 224b from openings 214a and 214b, respectively. Retainer portion 210a is moved towards 5 retainer portion 210b in a direction 60 and retainer portion 210b is moved towards retainer portion 210a in a direction 61 in order to latch clip 224b to opening 214a and latch clip 224a to opening 214b. FIG. 3 additionally illustrates a close up view of braking mechanism 211 (i.e., comprising braking mechanism portions 211a and 211b), optional motion detector sensor/alarm apparatus 200 (i.e., comprising motion detector sensor/alarm apparatus portions 218a and 218b), and optional electrical motor/signal receiving device 200 (i.e., comprising electrical motor/signal receiving device portions 200a and 200b). Each of braking mechanism portion 211a, motion detector sensor/alarm apparatus portion 218a, and electrical motor/signal receiving device portion 200a is mechanically attached to retainer portion 210a. Each of braking mechanism portion 211b, motion detector sensor/ 25 alarm apparatus portion 218b, and electrical motor/signal receiving device portion 200b is mechanically attached to retainer portion 210b.

FIG. 4A illustrates an alternative to FIG. 3, in accordance with embodiments of the present invention. In contrast to FIG. 3, FIG. 4A illustrates retainer portion 8a removably attached to retainer portion 8b using clips 11a and 11b removably attached to openings 15a and 15b. Additionally, FIG. 4 illustrates cut away line 5A-5A applicable to the cross sectional views of FIGS. 4B-4D as described *infra*.

FIG. 4B illustrates a cross sectional view of retainer apparatus 8 taken at cut away line 5A-5A of FIG. 4A, in accordance with embodiments of the present invention. FIG. 4B illustrates a cross sectional view of retainer portions 8a and 8b, braking mechanism portions 31a and 31b, electrical motor/signal receiving device portions 34a and 34b, and adjustable harness straps 4a and 4b. Braking mechanism portion 31a comprises a first section 37a and a second section 37b. In order to engage braking mechanism portion 31a, first section 37a is moved in direction 70 until contact is made with surface 61a of adjustable harness strap 4a and second section 37b is moved in direction 71 until contact is made with surface 61b of adjustable harness strap 4a. First section 37a is locked to second section 37b (i.e., upon contact with adjustable harness strap 4a to prevent movement of retainer portion 8b) using any means including, inter alia, clips, locking devices, screws, spring loaded latches (e.g., as described with respect to FIG. 4C, *infra*), magnetic means, an electro/mechanical device such as a solenoid or an electrical motor, etc. Additionally, first section 37a, surface 61a, second section 37b, and/or surface 61b may each include a frictional material (e.g., sandpaper type material, rubber, teeth (e.g., as illustrated in FIG. 4D, *infra*), etc) to create friction and cause resistance to movement. Alternatively, first section 37a, surface 61a, second section 37b, and/or surface 61b may each include a magnetic material (e.g., standard magnetic material, electromagnetic structure such as an electromagnet, etc) to cause resistance to movement. The aforementioned contact and locking process causes a resistance to movement between adjustable harness strap 4a (i.e., on any portion of adjustable harness strap 4a such as edge sections 67a and 67b or any surface of adjustable harness strap 4a) and braking mechanism portion 31a.

US 10,710,545 B2

7

31a thereby holding (or locking) retainer portion 8b in a stationary position at a user selected location anywhere on adjustable harness strap 4a. Braking mechanism portion 31b comprises a first section 38a and a second section 38b. In order to engage braking mechanism portion 31b, first section 38a is moved in direction 20 70 until contact is made with surface 62a of adjustable harness strap 4b and second section 38b is moved in direction 71 until contact is made with surface 62b of adjustable harness strap 4b. First section 38a is locked to second section 38b (i.e., upon contact with adjustable harness strap 4b to prevent movement of retainer portion 8a) using any means including, inter alia, clips, locking devices, screws, spring loaded latches (e.g., as described with respect to FIG. 4C, infra), magnetic means, a solenoid, etc. Additionally, first section 38a, surface 62a, second section 38b, and/or surface 62b may each include a frictional material (e.g., sandpaper type material, rubber, teeth (e.g., as illustrated in FIG. 4D, infra), etc) to create friction and cause resistance to movement. Alternatively, first section 38a, surface 62a, second section 38b, and/or surface 62b may each include a magnetic material (e.g., standard magnetic material, electromagnetic structure, etc) to cause resistance to movement. The aforementioned contact and locking process causes a resistance to movement between adjustable harness strap 4b (i.e., on any portion of adjustable harness strap 4b such as edge sections 67c and 67d or any surface of adjustable harness strap 4b) and braking mechanism portion 31b thereby holding (or locking) retainer portion 8a in a stationary position at user selected location anywhere on adjustable harness strap 4b.

FIG. 4C illustrates a first alternative cross sectional view of retainer apparatus 8 of FIG. 4B taken at cut away line 5A-5A of FIG. 4A, in accordance with embodiments of the present invention. In contrast to FIG. 4B, braking mechanism portion 31a comprises a latch (compression) mechanism 43a and a spring assembly 41a and braking mechanism portion 31b comprises a latch (compression) mechanism 43b and a spring assembly 41b. Latch mechanism 43a and spring 41a (i.e., compressed) are used to lock (or latch) first section 37a to second section 37b (i.e., as illustrated in FIG. 4C). In order to release first section 37a from second section 37b, latch mechanism 43a is disengaged from braking mechanism portion 31a and moved in a direction 46 thereby relieving pressure on first section 37a and second section 37b (and spring 41a). As latch mechanism 43a is moved in direction 46, compressed spring 41a is decompressed aiding in movement of latch mechanism 43a (in direction 46) and relieving pressure on first section 37a and second section 37b. The aforementioned process enables retainer portion 8b to slidably move along adjustable harness strap 4a. In order to lock or latch first section 37a to second section 37b (and enable braking mechanism portion 31a), latch mechanism 43a is moved in a direction 45 and locked to braking mechanism portion 31a thereby enabling pressure on first section 37a and second section 37b (and spring 41a). Latch mechanism 43b and spring 41b (i.e., compressed) are used to lock (or latch) first section 38a to second section 38b (i.e., as illustrated in FIG. 4C). In order to release first section 38a from second section 38b, latch mechanism 43b is disengaged from braking mechanism portion 31b and moved in a direction 47 thereby relieving pressure on first section 38a and second section 38b (and spring 41b). As latch mechanism 43b is moved in direction 47, compressed spring 41b is decompressed aiding in movement of latch mechanism 43b (in direction 47) and relieving pressure on first section 38a and second section 38b. The aforementioned process enables retainer portion 8a to slidably move along adjustable

8

harness strap 4b. In order to lock or latch first section 38a to second section 38b (and enable braking mechanism portion 31b), latch mechanism 43b is moved in a direction 48 and locked to braking mechanism portion 31b thereby enabling pressure on first section 38a and second section 38b (and spring 41b).

FIG. 4D illustrates a second alternative cross sectional view of retainer apparatus 8 of FIG. 4B taken at cut away line 5A-5A of FIG. 4A, in accordance with embodiments of the present invention. In contrast to FIG. 4B, first section 37a and/or second section 37b of braking mechanism portion 31a each comprise teeth (or any other type of gripping structure) to lock first section 37a and second section 37b to adjustable harness strap 4a to prevent movement of retainer portion 8b. Additionally, first section 38a and/or second section 38b of braking mechanism portion 31b each comprise teeth (or any other type of gripping structure) to lock first section 38a and second section 38b to adjustable harness strap 4b to prevent movement of retainer portion 8a.

FIG. 5A illustrates an alternative to FIG. 4A, in accordance with embodiments of the present invention. In contrast to FIG. 4A, adjustable harness strap 4a comprises a track apparatus 25 that includes tracks 25a-25c and adjustable harness strap 4b comprises a track apparatus 26 that includes tracks 26a-26c. Note that although FIG. 5A illustrates track apparatus 25 comprising three tracks (tracks 25a-25c) and track apparatus 26 comprising three tracks (tracks 26a-26c), any number of tracks may be used. Track apparatus 25 enables retainer portion 8b to move along adjustable harness strap 4a (and tracks 25a-25c). In order to disable movement of retainer portion 8b, braking mechanism portion 31a is enabled to cause resistance to movement between tracks 25a-25c and braking mechanism 31a (e.g., braking mechanism comprises braking portions that grab tracks 25a-25c) thereby holding (or locking) retainer portion 8b in a stationary position at a user selected location anywhere on adjustable harness strap 4a. Track apparatus 25 additionally enables electrical motor/signal receiving device portion 34a (i.e., an electrical motor portion) to ride along tracks 25a-25c upon receiving a user command (i.e., for automatically adjusting a position of retainer portion 8b). Electrical motor/signal receiving device portion 34a (i.e., an electrical motor portion) may additionally be disabled to cause resistance to movement between tracks 25a-25c and electrical motor/signal receiving device portion 34a to hold (or lock) retainer portion 8b in a stationary position at a user selected location anywhere on adjustable harness strap 4a (i.e., in addition to or instead of using braking mechanism portion 31a). Track apparatus 26 enables retainer portion 8a to move along adjustable harness strap 4b (and tracks 26a-26c). In order to disable movement of retainer portion 8a, braking mechanism portion 31b is enabled to cause resistance to movement between tracks 26a-26c and braking mechanism 31b (e.g., braking mechanism comprises braking portions that grab tracks 26a-26c) thereby holding (or locking) retainer portion 8a in a stationary position at a user selected location anywhere on adjustable harness strap 4b. Track apparatus 26 additionally enables electrical motor/signal receiving device portion 34b (i.e., an electrical motor portion) to ride along tracks 26a-26c upon receiving a user command (i.e., for automatically adjusting a position of retainer portion 8a). Electrical motor/signal receiving device portion 34b (i.e., an electrical motor portion) may additionally be disabled to cause resistance to movement between tracks 26a-26c and electrical motor/signal receiving device portion 34b to hold (or lock) retainer portion 8a in a stationary position at a user selected location anywhere on

US 10,710,545 B2

9

adjustable harness strap **4b** (i.e., in addition to or instead of using braking mechanism portion **31b**). Tracks **25a-25c** and **26a-26c** may comprise any type of or shaped track including, inter alia, vertical type tracks, rectangular shaped tracks, triangular shaped tracks, circular shaped tracks, a zipper type track, etc. Tracks **25a-25c** and **26a-26c** may comprise any type of material including, inter alia, plastic, metal, magnetic, a frictional material, etc. Additionally, FIG. **5A** illustrates cut away line **5B-5B** applicable to the cross sectional view of FIG. **5B** as described, infra.

FIG. **5B** illustrates a cross sectional view of retainer apparatus **8** taken at cut away line **5B-5B** of FIG. **5A**, in accordance with embodiments of the present invention. FIG. **5B** illustrates a cross sectional view of retainer portions **8a** and **8b**, braking mechanism portions **31a** and **31b**, electrical motor/signal receiving device portions **34a** and **34b**, tracks **25a-25c** and **26a-26c**, and adjustable harness straps **4a** and **4b**. Braking mechanism portion **31a** comprises a first section **52a** and a second section **52b**. In order to engage braking mechanism portion **31a**, second section **52b** (i.e., comprising braking devices on vertical sections of second section **52b**) is enabled such that pressure is applied (i.e., by the braking devices (e.g., spring loaded braking devices, solenoid driven braking devices, etc) on vertical sections of second section **52b**) to vertical sections of each of tracks **25a-25c** thereby causing a resistance to movement between tracks **25a-25c** (of adjustable harness strap **4a**) and braking mechanism portion **31a** (i.e., the braking devices on vertical sections of second section **52b**) thereby holding (or locking) retainer portion **8b** in a stationary position at a user selected location anywhere on adjustable harness strap **4a**. Alternatively, second section **52b** may comprise magnetic structures (e.g., electro/magnetic structures) on vertical sections of second section **52b** and tracks **25a-25c** comprise a metallic material capable of attraction to a magnetic field. In this case, engaging braking mechanism portion **31a** includes enabling the electro/magnetic structures on vertical sections of second section **52b** to generate a magnetic field thereby causing the electro/magnetic structures to magnetically hold the electro/magnetic structures to tracks **25a-25c**. The aforementioned process holds (or locks) retainer portion **8b** in a stationary position at a user selected location anywhere on adjustable harness strap **4a**. Braking mechanism portion **31b** comprises a first section **54a** and a second section **54b**. In order to engage braking mechanism portion **31b**, second section **54b** (i.e., comprising braking devices (e.g., spring loaded braking devices, solenoid driven braking devices, etc.) on vertical sections of second section **54b**) is enabled such that pressure is applied (i.e., by the braking devices on vertical sections of second section **54b**) to vertical sections of each of tracks **26a-26c** thereby causing a resistance to movement between tracks **26a-26c** (of adjustable harness strap **4b**) and braking mechanism portion **31b** (i.e., the braking devices on vertical sections of second section **54b**) thereby holding (or locking) retainer portion **8a** in a stationary position at a user selected location anywhere on adjustable harness strap **4b**. Alternatively, second section **54b** may comprise magnetic structures (e.g., electro/magnetic structures) on vertical sections of second section **54b** and tracks **26a-26c** comprise a metallic material capable of attraction to a magnetic field. In this case, engaging braking mechanism portion **31b** includes enabling the electro/magnetic structures on vertical sections of second section **54b** to generate a magnetic field thereby causing the electro/magnetic structures to magnetically hold the electro/magnetic structures to tracks **26a-26c**. The afore-

10

mentioned process holds (or locks) retainer portion **8a** in a stationary position at a user selected location anywhere on adjustable harness strap **4b**.

While embodiments of the present invention have been described herein for purposes of illustration, many modifications and changes will become apparent to those skilled in the art. Accordingly, the appended claims are intended to encompass all such modifications and changes as fall within the true spirit and scope of this invention.

What is claimed is:

1. A retainer apparatus comprising:

- a first retainer portion configured to be slidably attached to a first adjustable harness strap of a car seat;
- a second retainer portion configured to be slidably attached to a second adjustable harness strap of the car seat, wherein said first retainer portion is removably attached to said second retainer portion;
- a sensor comprising a motion detector and an alarm, wherein said motion detector is configured to detect movement of said retainer apparatus, and wherein said motion detector is configured to activate said alarm to alert a user in said vehicle if said movement of said retainer apparatus is detected; and
- a braking mechanism configured to resist said movement of said first retainer portion and said second retainer portion along said first adjustable harness strap and said second adjustable harness strap, wherein said braking mechanism comprises a braking device comprising braking portions configured for locking together thereby contacting opposite surfaces of said first adjustable harness strap and said second adjustable harness strap for applying resistance to said first adjustable harness strap and said second adjustable harness strap to hold at least one of said first retainer portion and said second retainer portion in a first stationary position along at least one of said first adjustable harness strap and said second adjustable harness strap, wherein said braking mechanism further comprises a locking portion configured to apply mechanical pressure and lock said braking portions of said braking device, and wherein said sensor and said braking mechanism are contained within at least one of said first retainer portion and said second retainer portion.

2. The retainer apparatus of claim 1, wherein said movement comprises at least one of: moving along said first adjustable harness strap and said second adjustable harness strap in a first vertical direction extending from lower attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively or moving along said first adjustable harness strap and said second adjustable harness strap in a second vertical direction extending from first upper attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively.

3. The retainer apparatus of claim 2, wherein said movement further comprises said first retainer portion being disconnected from said second retainer portion.

4. The retainer apparatus of claim 2, wherein said first vertical direction comprises an opposite direction from said second vertical direction.

5. The retainer apparatus of claim 1, wherein said movement comprises said first retainer portion being disconnected from said second retainer portion.

6. The retainer apparatus of claim 1, further comprising: memory within said retainer apparatus, wherein said memory is configured to store distance data associated

US 10,710,545 B2

11

with distances with respect to said first retainer portion and said second retainer portion moving along said first adjustable harness strap and said second adjustable harness strap.

7. The retainer apparatus of claim 1, wherein said retainer apparatus, said first adjustable harness strap and said second adjustable harness strap are comprised by a harness apparatus mechanically attached to said car seat, and wherein said harness apparatus is configured to restrain an occupant of said car seat and prevent said occupant from being ejected from said car seat.

8. The retainer apparatus of claim 1, wherein said braking mechanism further comprises a magnetic structure configured to apply said resistance.

9. A car seat apparatus comprising:

- a first adjustable harness strap;
- a second adjustable harness strap;

a retainer apparatus comprising a first retainer portion slidably attached to said first harness strap and a second retainer portion slidably attached to said second harness strap, wherein said first retainer portion is removably attached to said second retainer portion, wherein said retainer apparatus further comprises a sensor comprising a motion detector and an alarm, wherein said motion detector is configured to detect movement of said retainer apparatus, and wherein said motion detector is configured to activate said alarm to alert a user in said vehicle if said movement of said retainer apparatus is detected, wherein said retainer apparatus further comprises a braking mechanism configured to resist said movement of said first retainer portion and said second retainer portion along said first adjustable harness strap and said second adjustable harness strap, wherein said braking mechanism comprises a braking device comprising braking portions configured for locking together thereby contacting opposite surfaces of said first adjustable harness strap and said second adjustable harness strap for applying resistance to said first adjustable harness strap and said second adjustable harness strap to hold at least one of said first retainer portion and said second retainer portion in a first stationary position along at least one of said first adjustable harness strap and said second adjustable harness strap, wherein said braking mechanism further comprises a locking portion configured to apply mechanical pressure and lock said braking portions of said braking device, and wherein said sensor and said braking mechanism are contained within at least one of said first retainer portion and said second retainer portion; and

a car seat structure comprising a harness apparatus mechanically attached to a car seat, wherein said retainer apparatus, said first adjustable harness strap, and said second adjustable harness strap are comprised by said harness apparatus, and wherein said harness apparatus is configured to restrain an occupant of said car seat apparatus and prevent said occupant from being ejected from said car seat apparatus.

10. The car seat apparatus of claim 9, wherein said movement comprises at least one of: moving along said first adjustable harness strap and said second adjustable harness strap in a first vertical direction extending from lower attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively or moving along said first adjustable harness strap and said second adjustable harness strap in a second vertical direction extending from first upper

12

attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively.

11. The car seat apparatus of claim 10, wherein said movement further comprises said first retainer portion being disconnected from said second retainer portion.

12. The car seat apparatus of claim 10, wherein said first vertical direction comprises an opposite direction from said second vertical direction.

13. The car seat apparatus of claim 9, wherein said movement comprises said first retainer portion being disconnected from said second retainer portion.

14. The car seat apparatus of claim 9, further comprising: memory within said retainer apparatus, wherein said memory is configured to store distance data associated with distances with respect to said first retainer portion and said second retainer portion moving along said first adjustable harness strap and said second adjustable harness strap.

15. The car seat apparatus of claim 9, further comprising: an additional retainer apparatus comprising a third retainer portion slidably attached to said first harness strap and a fourth retainer portion slidably attached to said second harness strap, wherein said third retainer portion is removably attached to said fourth retainer portion, wherein said additional retainer apparatus further comprises an additional sensor comprising an additional motion detector and an additional alarm, wherein said additional motion detector is configured to detect additional movement of said additional retainer apparatus, wherein said additional motion detector is configured to activate said additional alarm to alert said user in said vehicle if said additional movement of said additional retainer apparatus is detected, and wherein said additional sensor is contained within at least one of said first retainer portion and said second retainer portion.

16. The car seat apparatus of claim 15, wherein said additional movement of said additional retainer apparatus comprises said third retainer portion being disconnected from said fourth retainer portion.

17. A retainer apparatus comprising:

- a first retainer portion configured to be slidably attached to a first adjustable harness strap of a car seat;
- a second retainer portion configured to be slidably attached to a second adjustable harness strap of the car seat, wherein said first retainer portion is removably attached to said second retainer portion; and
- a sensor comprising a motion detector and an alarm, wherein said motion detector is configured to detect movement of said retainer apparatus, wherein said motion detector is configured to activate said alarm to alert a user in said vehicle if said movement of said retainer apparatus is detected, and wherein said sensor is contained within at least one of said first retainer portion and said second retainer portion.

18. The retainer apparatus of claim 17, wherein said movement comprises at least one of: moving along said first adjustable harness strap and said second adjustable harness strap in a first vertical direction extending from lower attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively or moving along said first adjustable harness strap and said second adjustable harness strap in a second vertical direction extending from first upper

US 10,710,545 B2

13

attachment points of said first adjustable harness strap to said car seat and of said second adjustable harness strap to said car seat respectively.

19. The retainer apparatus of claim 18, wherein said movement further comprises said first retainer portion being 5 disconnected from said second retainer portion.

20. The retainer apparatus of claim 17, wherein said movement comprises said first retainer portion being disconnected from said second retainer portion.

* * * * *

10

14



US010710545C1

(12) **EX PARTE REEXAMINATION CERTIFICATE** (12354th)
United States Patent
Friedman

(10) **Number:** **US 10,710,545 C1**
 (45) **Certificate Issued:** ***Aug. 14, 2023**

(54) **LOCKING HARNESS**

(71) Applicant: **FRIEDMAN IP HOLDINGS, LLC**,
 Niskayuna, NY (US)

(72) Inventor: **Mark J. Friedman**, Niskayuna, NY
 (US)

(73) Assignee: **FRIEDMAN IP HOLDINGS, LLC**,
 Niskayuna, NY (US)

Reexamination Request:

No. 90/014,627, Dec. 10, 2020

Reexamination Certificate for:

Patent No.: **10,710,545**
 Issued: **Jul. 14, 2020**
 Appl. No.: **16/273,291**
 Filed: **Feb. 12, 2019**

(*) Notice: This patent is subject to a terminal disclaimer.

Related U.S. Application Data

(60) Continuation of application No. 15/602,294, filed on May 23, 2017, now Pat. No. 10,259,423, which is a continuation of application No. 14/984,232, filed on Dec. 30, 2015, now Pat. No. 9,669,797, which is a continuation of application No. 14/481,016, filed on Sep. 9, 2014, now Pat. No. 9,561,776, which is a division of application No. 13/653,540, filed on Oct. 17, 2012, now Pat. No. 8,851,575, which is a division of application No. 12/703,227, filed on Feb. 10, 2010, now Pat. No. 8,333,433.

(51) **Int. Cl.**
B60R 22/48 (2006.01)
B60R 22/10 (2006.01)
B60N 2/28 (2006.01)

B60R 22/12 (2006.01)
B60R 22/36 (2006.01)

(52) **U.S. Cl.**
 CPC **B60N 2/2812** (2013.01); **B60N 2/2803**
 (2013.01); **B60R 22/105** (2013.01); **B60R**
22/12 (2013.01); **B60R 22/36** (2013.01); **B60R**
22/48 (2013.01); **A44D 2200/12** (2013.01);
B60N 2002/2815 (2013.01); **Y10S 24/38**
 (2013.01); **Y10T 24/4012** (2015.01); **Y10T**
24/45529 (2015.01); **Y10T 29/49826** (2015.01)

(58) **Field of Classification Search**

None

See application file for complete search history.


(56) **References Cited**

To view the complete listing of prior art documents cited during the proceeding for Reexamination Control Number 90/014,627, please refer to the USPTO's Patent Electronic System.

Primary Examiner — Sara S Clarke

(57) **ABSTRACT**

A retainer apparatus including a first retainer portion, a second retainer portion, and a sensor comprising a motion detector and an alarm. The retainer apparatus includes the first retainer portion configured to be slidably attached to a first harness strap and a second retainer portion configured to be slidably attached to a second harness strap. The first retainer portion is removably attached to the second retainer portion. The motion detector is configured to detect movement of the retainer apparatus and activate the alarm to alert a user in a vehicle if movement of the retainer apparatus is detected.



US 10,710,545 C1

1

2

**EX PARTE
REEXAMINATION CERTIFICATE**

THE PATENT IS HEREBY AMENDED AS
INDICATED BELOW.

5

AS A RESULT OF REEXAMINATION, IT HAS BEEN
DETERMINED THAT:

The patentability of claim **20** is confirmed.

10

Claim **17** is cancelled.

Claims **1-16, 18** and **19** were not reexamined.

* * * * *